



AVANTAGE PRODUIT - PRODUCT ADVANTAGE

POTEAU 5 trous COMPLET, livré monté. Support de main courante orientable et réglable en hauteur (+30mm max)

Inoline, une ligne qui design votre maison. Ultra contemporaine, la ligne aéro-fuselée du garde-corps Inoline dessine et restructure architecturalement escaliers, mezzanines, terrasses, balcons...

5 drillings COMPLETE POST, supplied mounted. Swivel and adjustable handrail bracket (+30mm max)

Inoline, a line made to design your home. Ultra contemporary, the aerodynamic look of Inoline railings redesigns and restructures staircases, mezzanines, terraces, balconies.....

CARACTERISTIQUES TECHNIQUES - SPECIFICATIONS

	poteau - post 35 x 55 x H966 mm
dimensions hors tout overall dimensions	platine au sol - floor plate 110 x 120 mm
	support de main courante - handrail bracket Ø14 x H127 mm

MATIERE - MATERIAL

	aluminium corps poteau post structure
matière + traitement material + treatment	fonte d'aluminium - cast aluminium support main courante handrail bracket
	acier - steel platine au sol + visserie post foot + fastenings
	poli - polished structure poteau post structure
traitement - finition treatment - finishing	thermolaqué RAL9006 - powder coated RAL9006 support main courante + platine au sol handrail bracket + post foot
provenance origin	inox - stainless steel visserie fastenings China China

LOGISTIQUE - LOGISTIC

gencod	3 443 440 007 630	livré supplied	monté - mounted
conditionnement packaging	1	colis package	2,71 kg 12,5 x 11,3 x 97,2cm
poids unité de vente weight unit sale	2,71kg	palette de transport transport pallet	

INFORMATIONS COMPLEMENTAIRES - OTHER INFORMATION

utilisation use	intérieure + extérieure indoor + outdoor
autres informations accessoires fournis -- other informations accessories supplied	Perçages platine au sol: Ø11mm (x4) Ground mounting plate drillings: Ø11mm (x4) -- Support de main courante intégré au poteau pivotant et réglable en hauteur (+30mm maxi). Handrail support integrated to the post, rotating and adjustable height (+ 30mm max) . -- Platine de fixation au sol intégrée au poteau. Ground mounting plate integrated to the post.
conseils installation installation advice	Règlementation: L'entraxe poteaux ne doit pas dépasser 1000mm, accessoires de fixation inclus hors fixation au sol, à choisir selon la nature du sol. -- Regulation: The space between posts must not exceed 1000mm, mounting accessories included excluding floor mounting kits, to be selected according to the type of floor.