



**CARACTERISTIQUES TECHNIQUES - SPECIFICATIONS**

dimensions hors tout overall dimensions	L 2000mm x H1009 mm
dimensions main courante handrail dimensions	31 x 50 x 2000 mm (x1)
dimensions poteaux posts dimensions	50 x 70 x 984 mm (x2) support poteau au sol - post foot 110 x 120 x 260mm platine main courante - handrail plate 50 x 170 x 115mm
dimensions traverse cross-piece dimensions	20 x 32 x 845 mm (x10)

**MATIERE - MATERIAL**

matière material	hêtre - beech (traverses-poteaux-main courante cross pieces - posts - handrail) -- acier - steel (embouts de finition - support de poteau endcaps - post bracket) -- caoutchouc + plastique - rubber + plastic (accessoires de fixation panneau - accessories for panel fixing)
traitement - finition treatment - finishing	naturel non traité - natural untreated (hêtre - beech) -- noir + traité anti-corrosion + thermolaquage noir mat black + anti-corrosion treated + mat black thermo lacquered (acier - steel)
certification	FSC
provenance origin	Ukraine

**LOGISTIQUE - LOGISTIC**

gencod	3 443 440 000 860
conditionnement packaging	1
poids unité de vente weight unit sale	15kg

**AVANTAGE PRODUIT -PRODUCT ADVANTAGE**

**BOIS & HAUTE SECURITE :**  
NERO répond aux normes de sécurité en vigueur NF P 01-012 et NF P 01-013 (avec l'option panneau en verre synthétique ref.88).

Le garde-corps NERO est le premier garde-corps BURGER développé pour allier chaleur du bois et haute sécurité, dans un usage aussi bien privé que public.

**MISE EN PLACE ULTRA FACILE:** Calculez simplement le nombre de packs prêt à poser de 2m (remplissage traverses bois ou tubes acier) et si besoin, en fonction de la longueur totale de votre projet, finalisez votre balustrade avec le poteau supplémentaire (ref.85)

----

**WOOD & HIGH SECURITY:**  
NERO complies with current NF P 01-012 & NF P 01-013 safety standards (with optional synthetic glass panel ref 88).

The NERO railing is the first BURGER railing developed to combine the heat of wood and high security, for a private as well as for a public use.

**EASY SETTING:** simply calculate the bumbers of ready-made packs of 2 meters (infill with wooden cross-pieces or with steel tubes), and if necessary, regarding the total length of your project, finalize your railing with the extra post (ref.85).

**COLIS - PACKAGE**

type	poids	long	prof	haut
type	weight	length	depth	height
	15kg	202 x	12,5 x	11 cm
			x	
			x	

**CONDITIONNEMENT  
PACKAGING**

**INFORMATIONS COMPLEMENTAIRES - OTHER INFORMATION**

utilisation use	intérieure indoor	x	extérieure outdoor	
composition du pack pack content	10 traverses + accessoires de fixation pour panneau verre synthétique (réf.88) 1 main courante + 2 embouts de finition 2 poteaux (supports de poteau directement intégrés dans les poteaux) -- 10 cross pieces + fitting accessories for optional acrylic glass panel (ref.88) 1 handrail + 2 end caps 2 posts (post foot directly integrated into the posts)			

Adaptez votre garde corps aux normes, pour une hauteur de chute supérieure à 1m, usage privé & public NF P 01-012 / NF P 01-013:  
Panneau transparent de protection, à fixer sur la partie basse du garde corps (réf.88) (accessoires pour la fixation de ce panneau fourni dans ce pack réf.86).  
Traverses et main courante recoupables.

conseils installation  
installation advice

Règlementation: l'entraxe poteaux ne doit pas dépasser 915mm, accessoires de fixation inclus hors fixation au sol, à choisir selon la nature du sol.

Adapt your handrail to the standard for a fall height over 1m, for private & public use NF P 01-012 / NF P 01-013:  
Transparent panel for lowel protection, to fix to the bottom of the railing (ref.88) (accessories for this panel fixing included in this pack ref.86)

Regulation: the space between each spindle must not exceed 915mm, mounting accessories included excluding floor mounting kits, to be selected according to the type of floor.  
Crosse pieces and handrail are cuttable.

## PACKAGING

